



PRÜFNUMMER
201501009

Jointless large-area flooring system especially for animal clinics

- special and permanent softness due to the three functional layers (rubber-foam-rubber)
- the specially designed lower rubber mat adapts to every load condition
- high softness due to the foam inlay
- the system supports safe standing up and lying down
- the seamless top covering is easy to clean and disinfect
- frame profile surrounds the system reliably

Installation: according to BELMONDO® installation instructions*

Dimensions:

Complete system:

Thickness: 65 mm

Width x Length: max. 525 x 600 cm

consists of:

- **BELMONDO® Kingsize Cover**
 - **Thickness:** 15 mm
 - **Width x Length:** 262/348/440/525 cm x 250 cm - 600 cm in 10 cm increments
- **KRAI-PUR**
 - **Thickness:** 25 mm
 - **Width:** 120 cm
 - **Length:** 155 cm
- **BELMONDO® Cup**
 - **Thickness:** 25 mm
 - **Width:** 120 cm
 - **Length:** 130 cm
- **VITA Border**
 - **Height:** 6 cm
 - **Width:** 7 cm
 - **Length:** 240 cm

Accessories:

- **VITA Top »**
 - **Height:** 5 cm
 - **Width:** 5.5 cm
 - **Length:** 200 cm

Ground prerequisites: concrete, minimum 10 cm thick and smooth

* Please take notice of the corresponding specifications and installation instructions with useful advice and tips.

Gummiwerk KRAIBURG Elastik GmbH & Co. KG

Göllstraße 8 • 84529 Tittmoning • Deutschland • Tel.: +49 8683 701-527 • Fax: +49 8683 701-4527 • E-Mail: belmondo@kraiburg-elastik.de • www.kraiburg-belmondo.de

September 2016



proven pebbled profile on upper side



thickness:

+3/-2 mm

length + width:

+/- 1.5 % (DIN ISO 3302-1 tolerance class M4)

The tolerances also apply within the mat.

The products presented here generally should only be used for the listed applications. Technical specifications are subject to alterations. All sales are subject to our General Terms and Conditions. Legal basis is the German version of the document.